

# AGGANCI RAPIDI A LEVE - AISI316 - Bronzo fuso - Alluminio - Polipropilene QUICK COUPLING - Stainless steel - bronze - aluminium alloy - PP

Dimensionamenti secondo / Dimension according : Mill C-27487

**A** Adattatore filettato femmina  
Adaptor femal thread.  
Codice/Code : 0002x01

Dim	D	E	K	h	H
1/2"	32	14	32	26	41
3/4"	32	19	38	26	41
1"	37	24	41	32	49
1 1/4"	45	29	51	41	54
1 1/2"	53	37	57	42	55
2"	63	46	71	48	64
2 1/2"	76	55	84	50	70
3"	92	73	100	50	70
4"	120	98	129	53	80
5"	146	122	168	55	79
6"	176	148	192	60	86

**F** Adattatore filettato maschio o a saldare di testa  
Adaptor male thread or BW  
Codice:0002x06

Dim	D	E	K	h	H
1/2"	32	14	32	26	55
3/4"	32	10	38	26	55
1"	37	24	41	32	65
1 1/4"	45	29	51	41	76
1 1/2"	53	37	57	42	79
2"	63	46	71	48	86
2 1/2"	76	55	84	50	97
3"	92	73	100	50	100
4"	120	98	129	53	114
5"	146	122	168	55	117
6"	186	148	192	60	129

**B** Accoppiatore filettato maschio o a saldare di testa  
Coupler male thread or BW  
Codice / Code : 0002x02

Dim	A	B	C	F	h	H
1/2"	116	50	32	16	33	52
3/4"	116	50	32	22	33	52
1"	125	60	37	26	40	62
1 1/4"	177	80	46	35	49	67
1 1/2"	188	89	53	38	48	70
2"	197	97	63	50	52	79
2 1/2"	210	110	76	61	57	89
3"	248	135	92	75	60	91
4"	280	165	120	94	60	102
5"	306	190	146	117	65	105
6"	595	254	176	142	70	115

**DC** Accoppiatore tappo – Adaptor dust cap.  
Codice:0002x07

Dim	A	B	C	L	h	H
1/2"	-	-	-	-	-	-
3/4"	116	50	32	13	32	45
1"	125	60	37	15	41	56
1 1/4"	177	80	46	16	51	67
1 1/2"	188	89	53	18	51	69
2"	197	97	63	18	57	75
2 1/2"	210	110	76	20	60	80
3"	248	135	92	20	60	80
4"	280	165	120	20	62	82
5"	306	190	146	20	65	85
6"	595	254	176	20	70	90

**C** Accoppiatore portagomma – Coupler hose shank.  
Codice / Code : 0002x03

Dim	A	B	C	F	I	h	H
1/2"	-	-	-	-	-	-	-
3/4"	116	50	32	14	21	33	84
1"	125	60	37	20	27	40	98
1 1/4"	177	80	46	25	34	49	103
1 1/2"	188	89	53	32	41	48	106
2"	197	97	63	45	53	55	127
2 1/2"	210	110	76	57	67	57	137
3"	248	135	92	67	79	59	160
4"	280	165	120	89	105	62	170
5"	306	190	146	114	134	65	189
6"	595	254	176	142	157	70	214

**DP** Adattatore tappo – Coupler dust plug.  
Codice:0002x08

Dim	D	E	L	h	H
1/2"	-	-	-	-	-
3/4"	32	19	13	27	40
1"	37	24	15	33	48
1 1/4"	45	29	16	42	58
1 1/2"	53	37	18	43	61
2"	63	46	20	49	69
2 1/2"	76	55	20	51	71
3"	92	73	20	51	74
4"	120	98	20	54	79
5"	146	122	25	54	79
6"	176	148	25	60	85

**D** Accoppiatore filettato femmina – Coupler hose thread. Codice / Code : 0002x04

Dim	A	B	C	F	h	H
1/2"	116	50	32	16	32	51
3/4"	116	50	32	22	32	51
1"	125	60	37	26	42	62
1 1/4"	177	80	46	35	50	71
1 1/2"	188	89	53	38	51	71
2"	197	97	63	50	55	75
2 1/2"	210	110	76	61	56	86
3"	248	135	92	75	61	89
4"	280	165	120	94	62	95
5"	306	190	146	117	65	100
6"	295	254	176	142	70	115

Disponibili il tipo B ed il tipo F con  
attacchi a saldare di testa.

**E** Adattatore portagomma – Adaptor hose shank.  
Codice / Code : 0002x05

Dim	D	E	F	I	J	h	H
1/2"	-	-	-	-	-	-	-
3/4"	32	19	14	21	33	41	92
1"	37	24	20	27	39	47	106
1 1/4"	45	29	25	34	48	55	113
1 1/2"	53	37	31	40	56	57	117
2"	63	46	43	53	66	60	130
2 1/2"	76	55	55	67	80	67	146
3"	92	73	67	79	102	67	168
4"	120	98	92	105	133	70	178
5"	146	122	117	134	158	73	200
6"	176	148	142	158	183	78	220

A richiesta forniamo anche i tipi LAS ed LBS.

